

Datasheet Conveyor Belt

NITTA BELT TYPE: 2 SRAFP 02/W IM Nitta Japan code:	BELT NO.: 2185	
--	---------------------------------	---

Construction:	2 plies fray-less polyester, rigid, antistatic, spun
----------------------	--

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PU	PU	Impregnated antistatic fabric	
Thickness approx.:	0,2 mm 0,008 inch		- mm	- inch
Colour:	White	White	-	
Hardness:	92 Shore A		-	
Profile:	Glossy		-	

Total thickness approx.:	1,5	mm	0,059	inch
Weight approx.:	1,8	kg/m ²	0,36	lbf/ft ²
Max. width:	3000	mm	118,11	inch
Belt support:	Sliderbed (Rollers), Flat			
Rating at 1% elongation:	7	N/mm	40	lbf/inch
Advised pretension:	3 - 5	N/mm	17 to 28	lbf/inch
Maximum allowable tension:	8	N/mm	45	lbf/inch
Temperature range:	-20 to +80	°C	-4 to 176	°F
Minimum pulley diameters:				
Flexing:	15	mm	0,590	inch
Backflexing:	20	mm	0,78	inch

Special approval:	FDA, EU10/2011, Flame retardant: UL94HB		
Flame retardant: yes	Whisper bottom side: no	Extra Rigid: no	
Coefficient of friction to steel:	0,17		

Applications:	<p>Conveyor belt for the food industry</p> <p>This belt has frayless properties</p> <p>Cooling belt in bakeries</p> <p>Oil and grease resistant</p> <p>Conveyor belt in bakeries</p>
----------------------	--

Date of issue 30-10-2020-1