



Technical Data Sheet		Conveyor		
		Belt type	CC-12AK (2 LRF 704/001)	
Applications		<ul style="list-style-type: none"> • Conveyor belt for food industry • Cooling belt for bakeries 		
Item	Description	Remarks		
Specification	Construction			①PVC (White) ②PVC (White) ③PES Fabric (White)
Dimensions	Antistatic	No		
	Width	10 to 3,000 [mm]		
	Length	700 to 100,000 [mm]		
	Thickness	2.0 [mm]		
	Minimum pulley dia.	Finger Joint: \varnothing 30mm Skived Joint: \varnothing 50mm		
Properties	Tensile strength	80 [N/mm]		Test speed: 50 mm/min
	Elongation at break	12 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	0.5 [%]		
	Tension at 0.5%	2 [N/mm]		Ambient condition: 23°C,50%R.H.
	Operating temp.	Continuously: -10 to +70 [°C]		
		Periodically: -20 to +100 [°C]		
	Coefficient of friction	0.7 to 0.8 (Steel) PVC side 0.2 to 0.25 (Steel) Fabric side		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.
Mass	2.4 [kg/m ²]			
Features	<ul style="list-style-type: none"> • FDA approved • USDA approved • Oil resistant 			

NITTA CORPORATION OF AMERICA

The contents of this TDS may be changed without notice.