



Technical Data Sheet		NLG™		
		Belt type	GUF-12AK	
U-025		<ul style="list-style-type: none"> • Food Conveyor • Conveyor for middleweight material 		
Applications				
Item		Description		Remarks
Specification	Construction			<ul style="list-style-type: none"> ①PTFE sheet (Flat, gray) ②Polyurethane ③PES Fabric (White)
	Dimensions	Antistatic	No	
	Width	10 to 1,000 [mm]		
	Length	700 to 100,000 [mm]		
	Thickness	1.3 [mm]		
	Joint	Finger Joint or Skiver Joint		
Properties	Tensile strength	120 [N/mm]		Test speed : 50 mm/min
	Elongation at break	15 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	0.5 [%]		
	Tension at 0.5 [%]	2 [N/mm]		Ambient condition: 23°C,50%R.H.
	Minimum pulley dia.	φ50 [mm] (Finger Joint) φ70 [mm] (Skiver Joint)		
	Operating temp.	-20 to 80 [°C]		
	Coefficient of friction	0.1 to 0.15(Steel) PTFE sheet side 0.2 to 0.25(Steel) Fabric side		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.
	Mass	1.3 [kg/m ²]		
Features	<ul style="list-style-type: none"> • Releasable. • We can't recommend for accumulation conveyor. 			