



Technical Data Sheet		NLG™			
		Belt type	WU-7DFT		
U-102		Applications			<ul style="list-style-type: none"> • Food conveyor • Conveyor for lightweight material
Item		Description		Remarks	
Specification	Construction			①PES Fabric (White)	
	Dimensions	Antistatic	Yes		
	Width	10 to 1,500 [mm]			
	Length	700 to 100,000 [mm]			
	Thickness	0.8 [mm]			
	Joint	Finger Joint or Skiver Joint			
Properties	Tensile strength	70 [N/mm]		Test speed : 50 mm/min	
	Elongation at break	35 [%]		Ambient condition: 23°C,50%R.H.	
	Standard elongation	0.3 [%]			
	Tension at 0.3 [%]	0.6 [N/mm]		Ambient condition: 23°C,50%R.H.	
	Minimum pulley dia.	φ15 [mm] (Finger Joint) φ20 [mm] (Skiver Joint)			
	Operating temp.	-20 to 80 [°C]			
	Coefficient of friction	0.2 to 0.25(Steel) Both side		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.	
	Mass	0.75 [kg/m ²]			
Features	<ul style="list-style-type: none"> • FDA adaptation. 				