



Technical Data Sheet		NLG™		
		UG-017	Belt type	
Applications		<ul style="list-style-type: none"> Inclined and declined conveyor Conveyor for lightweight material 		
Item		Description		Remarks
Specification	Construction			①Low-hardness polyurethane (Longitudinal groove pattern, Green) ②PES Fabric (White)
	Dimensions	Antistatic	Yes	
	Width	10 to 1,500 [mm]		
	Length	700 to 100,000 [mm]		
	Thickness	1.2 [mm]		
	Joint	Finger Joint or Skiver Joint		
Properties	Tensile strength	60 [N/mm]		Test speed : 50 mm/min
	Elongation at break	25 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	0.5 [%]		
	Tension at 0.5 [%]	1 [N/mm]		Ambient condition: 23°C,50%R.H.
	Minimum pulley dia.	ϕ 15 [mm] (Finger Joint) ϕ 20 [mm] (Skiver Joint)		
	Operating temp.	-20 to 80 [°C]		
	Coefficient of friction	Over 1.0(Steel) Polyurethane side 0.2 to 0.25(Steel) Fabric side		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.
	Mass	1.0 [kg/m ²]		
Features	<ul style="list-style-type: none"> Top surface is high friction. 			