



Technical Datasheet	Conveyor Belt	
	Belt type	UG-010 Ver.6

Applications

- Material handling
- Food conveyance
- Medium duty conveyor

Construction



Top side	Bottom side
TPU	Polyester
0.4mm	-
Flat	Fabric
Green	White
Tension member	Splice
Polyester	Finger
Fabric	Skiver
2ply	
Construction	

Dimensions

Width/Roll (max.)	2,000mm
Width/Endless (max.)	2,000mm
Length (max.)	110m
Total thickness	1.4mm
Weight	1.5 kg/m ²

Please contact Nitta if you need other dimensions.

Regulatory compliance

Food Sanitation Act (Japan)
RoHS(2011/65/EC,
(EU)2015/863)

Features

Antistatic
Wider widths are available
Slider bed
Roller bed

Properties

Minimum pulley diameter

Flexing	
Finger	15mm
Skiver	40mm
Back flexing	
Finger	20mm
Skiver	40mm
Knife edge	-

Dynamic properties

Standard elongation	0.5%
Tension after relaxation at 0.5%	2.0N/mm
Initial tension at 1.0%	8.0N/mm
Tension after relaxation at 1.0%	4.0N/mm
Operating temperature range	-20~80°C
Operating temperature range*	-20~80°C

*When under continuous use

Tensile properties

Tensile strength	120N/mm
Elongation at break	15%
Maximum allowable tension	8.0N/mm
Maximum allowable elongation	1.0%

Coefficient of friction

Top	vs. Steel	0.5~0.6
	vs. Paper	0.6~0.7
Bottom	vs. Steel	0.1~0.3
	vs. Lagged pulley	0.3~0.6
	vs. POM (resin)	0.1~0.4