


Technical Datasheet		Conveyor Belt	
Belt type		GU-16D-G	
		UG-008 Ver.7	
Applications ▪ Material handling ▪ Accumulation conveyor ▪ Medium duty conveyor			
Construction			
	Top side		Bottom side
	Polyester		Polyester
	-		-
	Fabric		Fabric
	Green		White
	Tension member		Splice
	Polyester		Finger
	Fabric		Skiver
	2ply		
	Construction		
Dimensions			
Width/Roll (max.)		2,000mm	
Width/Endless (max.)		2,000mm	
Length (max.)		100m	
Total thickness		1.4mm	
Weight		1.2 kg/m ²	
Please contact Nitta if you need other dimensions.			
Regulatory compliance			
RoHS(2011/65/EC, (EU)2015/863)			
Features			
Antistatic			
Accumulation			
Wider widths are available			
Slider bed			
Roller bed			
Properties			
Minimum pulley diameter			
Flexing			
Finger		50mm	
Skiver		60mm	
Back flexing			
Finger		50mm	
Skiver		60mm	
Knife edge		-	
Dynamic properties			
Standard elongation		0.5%	
Tension after relaxation at 0.5%		3.0N/mm	
Initial tension at 1.0%		12.0N/mm	
Tension after relaxation at 1.0%		6.0N/mm	
Operating temperature range		-20~80°C	
Operating temperature range*		-20~80°C	
*When under continuous use			
Tensile properties			
Tensile strength		160N/mm	
Elongation at break		15%	
Maximum allowable tension		12.0N/mm	
Maximum allowable elongation		1.0%	
Coefficient of friction			
Top	vs. Steel	0.2~0.4	
	vs. Paper	0.3~0.5	
Bottom	vs. Steel	0.1~0.3	
	vs. Lagged pulley	0.3~0.6	
	vs. POM (resin)	0.1~0.4	
NITTA CORPORATION			

※The contents of this Technical Data Sheet may be changed without notice.