

Technical Datasheet	Conveyor Belt	
	Belt type	GU-9A
		U-013 Ver.5

Applications

- Material handling
- Food conveyance
- Light duty conveyor

Construction



Top side

TPU
0.3mm
Matte surface
Green

Bottom side

Polyester
-
Fabric
White

Tension member

Polyester
Fabric
2ply

Splice

Finger
Skiver

Construction



Dimensions

Width/Roll (max.)	1,000mm
Width/Endless (max.)	1,000mm
Length (max.)	100m
Total thickness	1.1mm
Weight	1.1 kg/m ²

Please contact Nitta if you need other dimensions.

Regulatory compliance

Food Sanitation Act (Japan)
RoHS(2011/65/EC,
(EU)2015/863)

Features

Antistatic
Low bending stress/High flexibility
Slider bed
Roller bed

Properties

Minimum pulley diameter

Flexing	
Finger	15mm
Skiver	40mm
Back flexing	
Finger	20mm
Skiver	40mm
Knife edge	
Finger	R5

Dynamic properties

Standard elongation	0.5%
Tension after relaxation at 0.5%	1.5N/mm
Initial tension at 1.0%	6.0N/mm
Tension after relaxation at 1.0%	3.0N/mm
Operating temperature range	-20~80°C
Operating temperature range*	-20~80°C

*When under continuous use

Tensile properties

Tensile strength	90N/mm
Elongation at break	15%
Maximum allowable tension	6.0N/mm
Maximum allowable elongation	1.0%

Coefficient of friction

Top	vs. Steel	0.4~0.5
	vs. Paper	0.5~0.6
Bottom	vs. Steel	0.1~0.3
	vs. Lagged pulley	0.3~0.6
	vs. POM (resin)	0.1~0.4