


Technical Datasheet		Conveyor Belt	
Belt type		WEXU-14ANS	
		U-144 Ver.7	
Applications - Food conveyance - Medium duty conveyor - Dough conveyor - Meat, broiler conveyance - Sliced vegetable conveyance			
Construction			
	Top side		Bottom side
	TPU		Special fabric
	0.3mm		-
	Matte surface		-
	White		White
	Tension member		Splice
	Polyester		Finger
	Fabric		Skiver
	3ply		
	Construction		
Dimensions			
Width/Roll (max.)		1,000mm	
Width/Endless (max.)		1,000mm	
Length (max.)		100m	
Total thickness		1.6mm	
Weight		1.9 kg/m²	
Please contact Nitta if you need other dimensions.			
Regulatory compliance			
Food Sanitation Act (Japan)			
RoHS(2011/65/EC,			
(EU)2015/863)			
Features			
Antistatic			
Sodium hypochlorite resistance			
Heat and moisture resistance			
Anti-microbial and Anti-mold			
Non-fray fabric			
Minimal shrinkage/foreign material			
Slider bed			
Roller bed			
Properties			
Minimum pulley diameter			
Flexing			
Finger		25mm	
Skiver		40mm	
Back flexing			
Finger		35mm	
Skiver		40mm	
Knife edge			
Finger		R5	
Dynamic properties			
Standard elongation		0.5%	
Tension after relaxation at 0.5%		2.3N/mm	
Initial tension at 1.0%		9.2N/mm	
Tension after relaxation at 1.0%		4.6N/mm	
Operating temperature range		-20~100°C	
Operating temperature range*		-20~80°C	
*When under continuous use			
Tensile properties			
Tensile strength		140N/mm	
Elongation at break		15%	
Maximum allowable tension		9.2N/mm	
Maximum allowable elongation		1.0%	
Coefficient of friction			
Top	vs. Steel	0.4~0.5	
	vs. Paper	0.5~0.6	
Bottom	vs. Steel	0.1~0.2	
	vs. Lagged pulley	0.3~0.5	
	vs. POM (resin)	0.1~0.3	
NITTA CORPORATION			