

Technical Datasheet		Conveyor Belt	
Belt type		WU-6A	
		U-001 Ver.5	
Applications - Food conveyance - Light duty conveyor - Dough conveyor			
Construction			
	Top side		Bottom side
	TPU		Polyester
	0.3mm		-
	Matte surface		Fabric
	White		White
	Tension member		Splice
	Polyester		Finger
	Fabric		Skiver
	1ply		
	Construction		
Dimensions		Properties	
Width/Roll (max.)		Minimum pulley diameter	
1,500mm		Flexing	
Width/Endless (max.)		Finger 10mm	
1,500mm		Skiver 20mm	
Length (max.)		Back flexing	
100m		Finger 15mm	
Total thickness		Skiver 20mm	
0.7mm		Knife edge	
Weight		Finger R2	
0.7 kg/m²		Dynamic properties	
Please contact Nitta if you need other dimensions.		Standard elongation	
Regulatory compliance		0.3%	
Food Sanitation Act (Japan)		Tension after relaxation at 0.3%	
RoHS(2011/65/EC,		0.6N/mm	
(EU)2015/863)		Initial tension at 1.0%	
		4.0N/mm	
Features		Tension after relaxation at 1.0%	
Antistatic		2.0N/mm	
Slider bed		Operating temperature range	
Roller bed		-20~80°C	
		Operating temperature range*	
		-20~80°C	
		*When under continuous use	
		Tensile properties	
		Tensile strength	
		60N/mm	
		Elongation at break	
		15%	
		Maximum allowable tension	
		4.0N/mm	
		Maximum allowable elongation	
		1.0%	
		Coefficient of friction	
		Top vs. Steel	
		0.4~0.5	
		vs. Paper	
		0.5~0.6	
		Bottom vs. Steel	
		0.1~0.3	
		vs. Lagged pulley	
		0.3~0.6	
		vs. POM (resin)	
		0.1~0.4	
NITTA CORPORATION			