

Technical Datasheet		Conveyor Belt	
Belt type		WUH-6ANF	
		U-156 Ver.5	
Applications - Food conveyance - Light duty conveyor - Accumulation conveyor - Dough conveyor			
Construction			
	Top side		Bottom side
	Hard TPU		Polyester
	0.3mm		-
	Matte surface		Fabric
	White		White
	Tension member		Splice
	Polyester		Finger
	Fabric		Skiver
	1ply		
	Construction		
Dimensions			
Width/Roll (max.)		1,500mm	
Width/Endless (max.)		1,500mm	
Length (max.)		100m	
Total thickness		0.75mm	
Weight		0.8 kg/m²	
Please contact Nitta if you need other dimensions.			
Regulatory compliance		Properties	
Food Sanitation Act (Japan)		Minimum pulley diameter	
RoHS(2011/65/EC,		Flexing	
(EU)2015/863)		Finger 15mm	
		Skiver 30mm	
		Back flexing	
		Finger 20mm	
		Skiver 30mm	
		Knife edge	
		-	
		Dynamic properties	
		Standard elongation	
		0.3%	
		Tension after relaxation at 0.3%	
		0.3N/mm	
		Initial tension at 1.0%	
		2.0N/mm	
		Tension after relaxation at 1.0%	
		1.0N/mm	
		Operating temperature range	
		-20~80°C	
		Operating temperature range*	
		-20~80°C	
		*When under continuous use	
Features		Tensile properties	
Antistatic		Tensile strength	
Superior abrasion resistance		60N/mm	
Non-fray fabric		Elongation at break	
Minimal shrinkage/hot water		15%	
Accumulation		Maximum allowable tension	
Slider bed		2.0N/mm	
Roller bed		Maximum allowable elongation	
		1.0%	
		Coefficient of friction	
		Top vs. Steel	
		0.3~0.4	
		vs. Paper	
		0.4~0.5	
		Bottom vs. Steel	
		0.1~0.3	
		vs. Lagged pulley	
		0.3~0.6	
		vs. POM (resin)	
		0.1~0.4	
NITTA CORPORATION			