



Technical Datasheet		Conveyor Belt	
Belt type		MGC-14A	C-082 Ver.5
Applications - Material handling - Medium duty conveyor			
Construction			
	Top side		Bottom side
	PVC		Polyester
	0.4mm		-
	Mirror surface		Fabric
	Green		White
	Tension member		Splice
	Polyester		Finger
	Fabric		Skiver
	2ply		
	Construction		
Dimensions		Properties	
Width/Roll (max.)		Minimum pulley diameter	
3,000mm		Flexing	
Width/Endless (max.)		Finger 25mm	
3,000mm		Skiver 50mm	
Length (max.)		Back flexing	
100m		Finger 30mm	
Total thickness		Skiver 50mm	
2.1mm		Knife edge	
Weight		-	
2.4 kg/m²		Dynamic properties	
Please contact Nitta if you need other dimensions.		Standard elongation	
Regulatory compliance		0.5%	
RoHS(2011/65/EC,		Tension after relaxation at 0.5%	
(EU)2015/863)		2.0N/mm	
		Initial tension at 1.0%	
		8.0N/mm	
		Tension after relaxation at 1.0%	
		4.0N/mm	
		Operating temperature range	
		-5~70°C	
		Operating temperature range*	
		-5~70°C	
		*When under continuous use	
Features		Tensile properties	
Antistatic		Tensile strength	
High lateral rigidity		140N/mm	
Whisper		Elongation at break	
Cut resistance		20%	
Wider widths are available		Maximum allowable tension	
Slider bed		8.0N/mm	
Roller bed		Maximum allowable elongation	
		1.0%	
		Coefficient of friction	
		Top vs. Steel	
		0.7~0.8	
		vs. Paper	
		0.8~0.9	
		Bottom vs. Steel	
		0.1~0.3	
		vs. Lagged pulley	
		0.3~0.6	
		vs. POM (resin)	
		0.1~0.4	
NITTA CORPORATION			