

Datasheet Conveyor Belt




**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRF 2716 WT
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	1,6		-	mm (approx.)
Colour:	Nitta colour	Nitta colour	-	
Hardness:	35 Shore A		-	
Profile:	WT		-	

Total thickness: 4,2 **mm (approx.)**
Weight: 3,6 **kg/m² (approx.)**
Max. width: 2000 **mm**
Belt support: Sliderbed (Rollers), Flat

Rating at 1% elongation: 8 **N/mm**
Advised pretension: 4 - 7 **N/mm**
Maximum allowable tension: 17 **N/mm**
Temperature range: -10 **to** +80 **°C**

Minimum pulley diameters:
Flexing: 50 **mm**
Backflexing: 75 **mm**

Special approval: Not applicable

Applications: Inclined or declined conveyors
 Conveying of (corrugated) cardboard boxes

Date of issue 17-03-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com