



Technical Data Sheet P-212		NITTA BELT POLY		
		Belt type	XH-3S-3	
Applications		Belt for Foulder Gluer Machines		
Item		Description		Remarks
Specification	Construction			①Soft NBR (Textured Pattern, Blue) ②PA Fabric ③PA Film ④Soft NBR (Textured Pattern, Blue)
	Dimensions	Antistatic	Yes	
	Width	6 to 320 [mm]		
	Length	300 to 103,000 [mm]		
	Thickness	2.85 [mm]		
	Joint	1/20Slope Skived joint(diagonal joint) Adhesive Polybond A and NLG Bond		
Properties	Tensile strength	135 [N/mm]		Test speed: 50mm/min
	Elongation at break	20 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	1 [%]		
	Tension at 1 [%]	3.4 [N/mm]		Ambient condition: 23°C,50%R.H.
	Minimum pulley dia.	50 [mm]		
	Operating temp.	-20 to +80°C		
	Coefficient of friction	0.8 to 0.9(Paper) / 0.7 to 0.8(Steel) (Both side)		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.
	Mass	3.2 [kg/m <sup>2</sup> ]		
Features				

Industrial Products Div.