



Technical Datasheet		Conveyor Belt	
Belt type		KC	
		U-055 Ver.5	
Applications ▪ Accumulation conveyor ▪ Medium duty conveyor			
Construction			
	Top side	Bottom side	
	Polyamide	Polyamide	
	-	-	
	Fabric	Fabric	
	Blue	Blue	
	Tension member	Splice	
	Polyester	Skiver	
	Fabric		
	3ply		
	Construction		
Dimensions			
Width/Roll (max.)		1,000mm	
Width/Endless (max.)		1,000mm	
Length (max.)		100m	
Total thickness		1.4mm	
Weight		1.4 kg/m²	
Please contact Nitta if you need other dimensions.			
Regulatory compliance			
RoHS(2011/65/EC, (EU)2015/863)			
Features			
Antistatic			
Accumulation			
Slider bed			
Roller bed			
Properties			
Minimum pulley diameter			
Flexing			
Skiver		50mm	
		-	
Back flexing			
Skiver		50mm	
		-	
Knife edge			
		-	
Dynamic properties			
Standard elongation		0.5%	
Tension after relaxation at 0.5%		1.5N/mm	
Initial tension at 1.0%		6.0N/mm	
Tension after relaxation at 1.0%		3.0N/mm	
Operating temperature range		-20~80°C	
Operating temperature range*		-20~80°C	
*When under continuous use			
Tensile properties			
Tensile strength		200N/mm	
Elongation at break		20%	
Maximum allowable tension		6.0N/mm	
Maximum allowable elongation		1.0%	
Coefficient of friction			
Top	vs. Steel	0.1~0.3	
	vs. Paper	0.2~0.4	
Bottom	vs. Steel	0.1~0.3	
	vs. Lagged pulley	0.3~0.6	
	vs. POM (resin)	0.1~0.4	
NITTA CORPORATION			