



Technical Data Sheet		NITTA BELT POLY		
		Belt type	XH-750-6	
Applications		Belt for Foulder Gluer Machines		
P-057				
Item	Description		Remarks	
Specification	Construction			①Soft NBR (Textured Pattern, Blue) ②PA Fabric ③PA Film ④Soft NBR (Textured Pattern, Blue)
	Antistatic	Yes		
Dimensions	Width	6 to 320 [mm]		
	Length	500 to 50,000 [mm]		
	Thickness	6.25 [mm]		
	Joint	Skived joint Adhesive Polybond A and E		
	Tensile strength	225 [N/mm]		Test speed: 50mm/min
Properties	Elongation at break	20 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	1 [%]		
	Tension at 1 [%]	5.6 [N/mm]		Ambient condition: 23°C,50%R.H.
	Minimum pulley dia.	90 [mm]		
	Operating temp.	-20 to +80°C		
	Coefficient of friction	0.8 to 0.9(Paper) / 0.7 to 0.8(Steel) (Both side)		Measurement condition: 7kPa, 1mm/s Ambient condition: 23°C,50%R.H.
	Mass	7.6 [kg/m ²]		
Features				

Industrial Products Div.